Clean Earth Sampling Protocol Southern Florida

| WETHORS (4) ARAMETICAL AND STATE OF THE PROPERTY OF THE PROPE | | | | | | | |
|--|---|---------|--------------|----------------------------------|---------------------------------|----------------------------------|---------------|
| METHODS (1) | FREQUENCY | FLO-PRO | 9020 01 9023 | 6000/7000 F Composite Samples | 1311/6010 (Except VOHs - Gra | 8082A b Samples) | 8260B or 8021 |
| Used Hydraulic Oil, Used Oil, Mineral Oil | Less than 140 Tons | 1 | 1 | 1 | (2) | 1 | 1 |
| | 140 to 699 Tons | 3 | 3 | 3 | (2) | 3 | 3 |
| | 700 to 1399 Tons | 5 | 5 | 5 | (2) | 5 | 5 |
| | Every Additional 700 Tons Thereafter | 1 | 1 | 1 | (2) | 1 | 1 |
| Limit (mg/kg) | | | 1,000 | 0.5 mg/kg Detection Limit | | 50 (Detection Limit of 0.02 ppm) | |

⁽¹⁾ The methods provided are standard EPA methods. The method revisions are subject to change and the most current method should always be utilized by the laboratory.

⁽²⁾ TCLP may be required based on the Total Metals results.

NOTE - Based on current and historical site usage, additional analysis may be requested.